

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A method of Automatic Repeat reQuest (ARQ) control in a High Speed Downlink Packet Access (HSDPA) communication system, the method including:

transmitting control information from a first station to a second station;

commencing receipt of the control information at the second station;

checking whether the control information was received with error; and if so,

generating a negative acknowledgment (NACK) message for transmission to the first station, and

transmitting the negative acknowledgment (NACK) message from the second station to the first station on a common control channel,

wherein the control information is transmitted and received on the common control channel,

wherein the control information error checking and acknowledgment message generating is performed at the second station by carrying out processing operations within radio interface layer 1.

2. (original) A method according to claim 1, wherein the control information error checking is carried out by performing a cyclic redundancy check on the control information.

3. (previously presented) A method according to claim 1, wherein the control information error checking is carried out during receipt of an associated data packet.

4. (previously presented) A method according to claim 1, and further including:

terminating receipt of the associated data packet at the second station upon failure of the control information error checking by carrying out processing operations within radio interface layer 1.

5-6. (cancelled)

7. (currently amended) A communication station forming part of a High Speed Downlink Packet Access (HSDPA) communication system, the communication station including:

receiving means for receiving control information transmitted from another station; and

processing means for checking whether the control information was received with error; and if so,

generating a negative acknowledgment (NACK) message
for transmission to the first station, and

the processing means acts to transmit the negative
acknowledgment (NACK) message from the second station to the
first station on the common control channel,

wherein the processing means acts to transmit and
receive control information on a common control channel,

wherein the control information error checking and
acknowledgment message generating is performed at the second
station by carrying out processing operations within radio
interface layer 1.

8. (original) A communication station according to
claim 7, wherein the processing means acts to carry out the
control information error checking by performing a cyclic
redundancy check on the control information.

9. (previously presented) A communication station
according to claim 7, wherein processing means acts to carry out
the control information error checking during receipt of an
associated data packet.

10. (previously presented) A communication station according to claim 7, wherein the processing means acts to terminate receipt of the associated data packet at the second station upon failure of the control information error checking by carrying out processing operations within radio interface layer 1.

11-12. (cancelled)

13. (previously presented) A method according to claim 2, wherein the control information error checking is carried out during receipt of an associated data packet.

14. (previously presented) A communication station according to claim 8, wherein processing means acts to carry out the control information error checking during receipt of an associated data packet.